






Lineārais augu LED apgaismojums

Modelis	Attēls	Specifikācija			
CVK821-18x3W		item	Parameter	item	Parameter
		dimension	550x30x30mm	working temperature	-20°-50°
		input voltage	AC85-265v	ratio& layout	18x3w layout
		Chip size	45mil	lifespan	50000 hour
		working current	550ma	housing color	silver
		working Frequency	50-60hz	atacl power/ lumens	25w/1800lm
		packing size	680*100*80	G. W kg/pc	1.5kg/pcs
		ctn size		ratio& layout	red/blue14:4
		A85ST-27x3W		item	Parameter
dimension	850x30x30mm			working temperature	-20°-50°
input voltage	AC85-265v			ratio& layout	27x3w layout
Chip size	45mil			lifespan	50000 hour
working current	520ma			housing color	silver
working Frequency	50-60hz			atcal power/ lumens	39W/2200lm
packing size	130*100*80 KG			G. W kg/pc	1.8kg/pcs
ctn size				ratio& layout	red/blue21:6
A5112-36x3W				item	Parameter
		dimension	1150x30x30mm	working temperature	-20°-50°
		input voltage	AC85-265v	ratio& layout	64x3w layout
		Chip size	45mil	lifespan	50000 hour
		working current	520ma	housing color	silver
		工作频率 working Frequency	50-60hz	atcal/ lumens	55W/4400
		packing size	1450*100*80 4KG	G. W kg/pc	2.1kg/pcs
		ctn size		ratio& layout	red/blue28:8
		ART01-20x1W		Item:LX-GLT10 Power: 20W Input Voltage:86-264VAC Spectrum: Full Spectrum Led QTY:20*1W Housing Material:Aluminum+PC Packing size:170*110*1260mm IP44	
LKS-30T 25X3W				Item:LX-HWG-30B Power: 50W Input Voltage:86-264VAC Spectrum: Full Spectrum Led QTY:25*3W Housing Material: Aluminum IP: 65 Rating Packing Size:128*12.3*8.5cm	

