## LED gaismekļi

Underwater light				
1*1W LED			EL EL STATE OF THE	1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 1*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ42mm/height:73mm 5. With 30cm 2*0.75mm² wire
1*1W LED			011	1. Underwater light (Bracket version) stainless steel body; Clear tempered glass 2. 1*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ75mm/height:110mm 5. With 30cm 2*0.75mm² wire
1*1W LED			Ø73 86 Ø67	1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 1*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ73mm/height:98mm 5. With 30cm 2*0.75mm² wire
3*1W LED			150	1. Underwater light (Bracket version) stainless steel body; Clear tempered glass 2. 3*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ95mm/height:150mm 5. With 30cm 2*0.75mm² wire
3*1W LED			\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 3*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ100mm/height:75mm 5. With 30cm 2*0.75mm² wire

3403-7*1W LED			1. Underwater light (Bracket version) stainless steel body; Clear tempered glass 2. 7*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Ф145mm/height:170mm
7*1W LED		©150	5. With 30cm 2*0.75mm² wire  1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 7*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ150mm/height:110mm 5. With 30cm 2*0.75mm² wire
9*1W LED		181	1. Underwater light (Bracket version) stainless steel body; Clear tempered glass 2. 9*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ170mm/height:180mm 5. With 30cm 2*0.75mm <sup>2</sup> wire
9*1W LED		#F #168	1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 9*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ168mm/height:135mm 5. With 30cm 2*0.75mm² wire
12*1W LED			1. Underwater light (Bracket version) stainless steel body; Clear tempered glass 2. 12*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ190mm/height:180mm 5. With 30cm 2*0.75mm² wire
12*1W LED		92(9) 9199	1. Underwater light (recessed version) stainless steel body; Clear tempered glass; ABS Plastic fixing box 2. 12*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ209mm/height:115mm 5. With 30cm 2*0.75mm² wire

18*1W LED			<ol> <li>Underwater light (Bracket version)</li> <li>stainless steel body; Clear tempered glass</li> <li>18*1W LED, driver build-in</li> <li>IP68, Class III, AC 12V</li> <li>Dia:Φ214mm/height:220mm</li> <li>With 30cm 2*0.75mm² wire</li> </ol>
12*1W LED			1. Fountain light (underwater light) stainless steel body; Clear tempered glass 2. 12*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ210mm/height:80mm 5. With 30cm 2*0.75mm² wire 6. Suitable fountain D:Max.Φ52
9*1W LED		T W W W W W W W W W W W W W W W W W W W	1. Fountain light (underwater light) stainless steel body; Clear tempered glass 2. 9*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ180mm/height:80mm 5. With 30cm 2*0.75mm² wire 6. Suitable fountain D:Max.Φ42
6*1W LED			1. Fountain light (underwater light) stainless steel body; Clear tempered glass 2. 6*1W LED, driver build-in 3. IP68, Class III, AC 12V 4. Dia:Φ168mm/height:80mm 5. With 30cm 2*0.75mm² wire 6. Suitable fountain D:Max.Φ35
TH12 50DT		951 S 251	Waterproof transformers  1. Thermoplastic material and sealed by epoxy resin. Built-in recoverable thermal protctor.  2. Insulation class B, IP68 Rating voltage:220V-240V; output voltage:11.5V AC  3. 50W  4. Dia:Φ60mm/height:150mm
TH13 100DT			Waterproof transformers 1. Thermoplastic material and sealed by epoxy resin. Built-in recoverable thermal protctor. 2. Insulation class B, IP68 Rating voltage:220V-240V; output voltage:11.5V AC 3. 100W 4. Dia:Φ96mm/height:125mm

TH14 200DT

TH14 200DT

Waterproof transformers

1. Thermoplastic material and sealed by epoxy resin. Built-in recoverable thermal protctor.

2. Insulation class B, IP68
Rating voltage:220V-240V; output voltage:11.5V AC

3. 200W

4. Dia:Φ155mm/height:138mm