

LED Street Light						
No	Picture	Part No.	Power	Description	LED Chip	Driver Brand
			(W)			
Patent Design, Nice Appearance, Good Quality						
1		IK30	30W	1. AC100-240V, 50/60Hz 2. CCT: 2700-6500K 3. Color: Sliver or Black. 4. CRI: 70/80 optional 5. Size: 410*200*90mm 6. Lumens: 125lm/w 7. Warranty: 5 Years 8. IP Rating: IP65	LUMILEDS Philips 3030	 Meanwell HLG-40
		IK40	40W			
2		IK50	50W	1. AC100-240V, 50/60Hz 2. CCT: 2700-6500K 3. Color: Sliver or Black. 4. CRI: 70/80 optional 5. Size: 410*200*90mm 6. Lumens: 120lm/w 7. Warranty: 5 Years 8. IP Rating: IP65	LUMILEDS Philips 3030	 Meanwell HLG-60
		IK60	60W			
3		IK100	100W	1. AC100-240V, 50/60Hz 2. CCT: 2700-6500K 3. Color: Sliver or Black. 4. CRI: 70/80 optional 5. Lumens: 12000 LM 120lm/w 6. Warranty: 5 Years 7. IP Rating: IP65	LUMILEDS Philips 3030	 Meanwell HLG-100
4		IK120	120W	1. AC100-240V, 50/60Hz 2. CCT: 2700-6500K 3. Color: Sliver or Black. 4. CRI: 70/80 optional 5. Lumens: 14400 LM 120lm/w 6. Warranty: 5 Years 7. IP Rating: IP65	LUMILEDS Philips 3030	 Meanwell HLG-120
5		IK150	150W	1. AC100-240V, 50/60Hz 2. CCT: 2700-6500K 3. Color: Sliver or Black. 4. CRI: 70/80 optional 5. Lumens: 18000 LM 120lm/w 6. Warranty: 5 Years 7. IP Rating: IP65	LUMILEDS Philips 3030	 Meanwell HLG-150
6		IR15		1. Photocell Sensor 2. Voltage: 105-305V AC 3. Fail On/off 4. Time delay: 3-15s 5. Operating Temperature:-40℃--+70℃ 6. Lighting Level: 10%-30% based on customer request.		
6		IR17		1. Intelligent Photocell Sensor 2. Voltage: 105-305V AC 3. 0-10V dimming 4. Midnight sleeping time in hour LED decay compensation featured 6. Operating Temperature:-40℃--+70℃ 7. Lighting Level: 10%-30% based on customer request.		5.